	Ref #	Hits	Search Text	DBs
1	S1	106	verify$3 same shipping same data and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
2	S2	27	(verify$3 or confirm$3) same shipping adj3 data and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
3	S3	592	shipping adj3 data and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
4	S4	308	S3 and check$3	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
5	S5	41	shipping adj3 data same check$3 and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
6	S6	19	shipping adj3 data same verify$3 and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
7	S7	0	verify$3 adj3 (shipping adj3 data) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
8	S8	5	(verify$3 or check$3 or confirm$5) adj3 (shipping adj3 data) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
9	S9	0	(verify$3 or check$3 or confirm$5) adj3 (shipping adj3 data) same voucher and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
10	S10	0	(verify$3 or check$3 or confirm$5) adj3 (shipping adj3 data) and voucher and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
11	S11	0	(verify$3 or check$3 or confirm$5) adj3 (shipping adj3 data) same (error or mistake) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
12	S12	30	shipping adj3 data same error and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
13	S13	0	shipping adj3 data same error same reciev$5 and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
14	S14	5	shipping adj3 data same error same receiv$5 and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
15	S15	3	shipping adj3 data same error same receiv$5 and (database or rpository)and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
16	S16	3	shipping adj3 data same error same receiv$5 and (database or repository)and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
17	S17	1476 12	stor$5 with (specific or define$3 or designate$4 or explicit or particular) with (storage or memeory or database or repository or (data adj bank)) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
18	S18	4786 2	(shipping or mail or address) and stor$5 with (specific or define$3 or designate$4 or explicit or particular) with (storage or memeory or database or repository or (data adj bank)) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
19	S19	47862	(shipping or mail or address) and (stor$5 with (specific or define$3 or designate$4 or explicit or particular) with (storage or memeory or database or repository or (data adj bank))) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
20	S20	1584	verify same (shipping or mail or address) and (stor$5 with (specific or define$3 or designate$4 or explicit or particular) with (storage or memeory or database or repository or (data adj bank))) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
21	S21	10854	(verify$3 or confirm$3 or check$3) same (shipping or mail or address) and (stor$5 with (specific or define$3 or designate$4 or explicit or particular) with (storage or memeory or database or repository or (data adj bank))) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
22	S22	1101	(verify$3 or confirm$3 or check$3) same (shipping or mail or address) same (stor$5 with (specific or define$3 or designate$4 or explicit or particular) with (storage or memeory or database or repository or (data adj bank))) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
23	S23	47	(verify$3 or confirm$3 or check$3) same (shipping or mail or address) same (stor$5 with (specific or define$3 or designate$4 or explicit or particular) with (storage or memeory or database or repository or (data adj bank)) with (error or fault$4)) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
24	S24	117	stor$4 adj fault$4 adj data and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
25	S25	13	(stor$4 adj fault$4 adj data) same (shipping or mail or address) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
26	S27	5	((stor$4 or save$4) adj (error or fault$4) adj data) same (shipping or mail or address) same (verify$3 or confirm$3 or check$3) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
27	S26	56	((stor$4 or save$4) adj (error or fault$4) adj data) same (shipping or mail or address) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
28	S28	5	((stor$4 or save$4) adj (error or fault$4) adj data) same (ship$5 or mail$5) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
29	S29	5	((stor$4 or save$4) adj (error or fault$4) adj data) same (ship$5 or mail$3) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
30	S30	2	((stor$4 or save$4) adj (error or fault$4) adj data) same (ship$5 or mail) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
31	S31	2	((stor$4 or save$4) adj (error or fault$4) adj data) same (ship$5 or mail or post$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
32	S32	0	((stor$4 or save$4) adj (error or fault$4) adj data) same (ship$5 or mail$3) same (examin$5 or correct$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
33	S33	0	((stor$4 or save$4) adj (error or fault$4) adj data) same (ship$5 or mail$3) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
34	S34	0	((stor$4 or save$4) adj (error or fault$4) adj data) same (ship$5 or mail$3) same user and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
35	S35	133	((stor$4 or save$4) adj (error or fault$4) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
36	S36	2	((stor$4 or save$4) adj (error or fault$4) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) same user and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
37	S37	0	((stor$4 or save$4) adj (error or fault$4) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) WITH (user or sender) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
38	S38	0	((stor$4 or save$4) adj (error or fault$4) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) WITH (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
39	S39	2	((stor$4 or save$4) adj (error or fault$4) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) same (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
40	S41	2	((stor$4 or save$4) adj (error or fault$4 or wrong) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) same (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
41	S40	135	((stor$4 or save$4) adj (error or fault$4 or wrong) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
42	S42	21	((stor$4 or save$4) adj (error or fault$4 or wrong) adj data) same (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) and (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
43	S43	23	((stor$4 or save$4) adj (error or fault$4 or wrong) adj data) same (examin$5 or correct$4 or check$3 or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) and (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
44	S44	833	((stor$4 or save$4) with (error or fault$4) adj data) with (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
45	S45	12	((stor$4 or save$4) with (error or fault$4) adj data) with (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) with (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
46	S46	85	((stor$4 or save$4) adj2 (error or fault$4) with data) with (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) with (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
47	S47	4	((stor$4 or save$4) adj2 (error or fault$4) adj2 data) with (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) with (user or sender or client) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
48	S48	7378	(user or clinet or sender) with data with (examin$5 or correct$4 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) with (revis$6 or correct$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
49	S49	554	(user or clinet or sender) with data with (examin$5 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) with (revis$6 or correct$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
50	S50	528	(user) with data with (examin$5 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) with (revis$6 or correct$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
51	S51	31	(user) with data with (examin$5 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) with (revis$6) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
52	S52	142	(user or clinet or sender) near5 data near5 (examin$5 or check or scrutinz$4 or inspect$4 or study$4 or survey$4 or view$4) near5 (revis$6 or correct$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
53	S53	7	(user or clinet or sender) near5 data near5 (examin$5) near5 (revis$6 or correct$4) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
54	S54	448	(adjust$3 or revis$6 or correct$4) with (information or data) with ordering and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
55	S55	90	(adjust$3) with (information or data) with ordering and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
56	S56	0	checking with plurality with plants with areas with operations with system with single and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
57	S57	0	checking with plurality with plants with areas with operations with system and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
58	S58	159	checking with plants and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
59	S59	0	checking with plants with shipping and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
60	S60	18	checking with (plants or facilit$4) with shipping and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
61	S61	269	(plants or facilit$4) with shipping with system and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
62	S62	11	(plants or facilit$4) with shipping with system with central and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
63	S63	2	(plants or facilities) with shipping with system with central and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
64	S64	4	analyze with error$1 with faulty and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
65	S65	1	analyze with error$1 with faulty same data same display and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
66	S66	0	(route or transmit) with (error$1 or fault$1) with data with reciever and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
67	S67	5595	(route or transmit) with (error$1 or fault$1) with data and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
68	S68	68	(route or transmit) with (fault$1 adj data) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
69	S69	163	interface with database with order with information and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
70	S70	11	interface with database with (order adj information) and (@pd<"20001027" or @ad<"20001027" or @rlad<"20001027" or @prad<"20001027")	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB

	Ref #	Hits	Search Text	DBs
71	S71	0	"10016796".pa.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
72	S72	0	"016796".pa.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
73	S73	6	"016796".ap.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
74	S74	2	"6773347".pn.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB
75	S75	2	"5640684".pn.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB